

## Maintenance

### Final Filter Maintenance

The final membrane filter should also be replaced once a year under normal operating conditions. The Balston Grade 95 final filter is located inside the 75-83 and is easily replaced by first removing the 2 front panel screws. Then, remove the compression fittings using a 1/2" and a 7/16" open end wrench. Slide the 1/2" nut and plastic ferrule off both ends of the disposable filter. Discard the plastic ferrules and worn DFU. The 1/2" compression nuts are reusable; do not discard. The replacement final filter kit (P/N 75922), which is shipped with 1/4" plastic ferrules, can now be installed. Install the DFU with the flow arrow pointing to the outlet. Tighten the compression fittings one turn after finger tight. Do not use metallic ferrules with the disposable filter unit, as these will damage the plastic connections. Leak test the 75-83 after installing the GS Grade 95 final filter.



Parker Hannifin Corporation  
Filtration and Separation Division  
100 Ames Pond Drive, P.O. Box 1262  
Tewksbury, MA 01876-0962  
Tel: 978-858-0505 Fax: 978-858-0625

Parker Hannifin plc  
Hermitage Court, Hermitage Lane  
Maidstone, Kent ME16 9NT, England  
Tel: +44 (0) 1622-723300  
Fax: +44 (0) 1622-728703

75922  
©Parker Hannifin Corporation 1997, 2002  
Printed in U.S.A.

## Maintenance

### Final Filter Maintenance

The final membrane filter should also be replaced once a year under normal operating conditions. The Balston Grade 95 final filter is located inside the 75-83 and is easily replaced by first removing the 2 front panel screws. Then, remove the compression fittings using a 1/2" and a 7/16" open end wrench. Slide the 1/2" nut and plastic ferrule off both ends of the disposable filter. Discard the plastic ferrules and worn DFU. The 1/2" compression nuts are reusable; do not discard. The replacement final filter kit (P/N 75922), which is shipped with 1/4" plastic ferrules, can now be installed. Install the DFU with the flow arrow pointing to the outlet. Tighten the compression fittings one turn after finger tight. Do not use metallic ferrules with the disposable filter unit, as these will damage the plastic connections. Leak test the 75-83 after installing the GS Grade 95 final filter.



Parker Hannifin Corporation  
Filtration and Separation Division  
100 Ames Pond Drive, P.O. Box 1262  
Tewksbury, MA 01876-0962  
Tel: 978-858-0505 Fax: 978-858-0625

Parker Hannifin plc  
Hermitage Court, Hermitage Lane  
Maidstone, Kent ME16 9NT, England  
Tel: +44 (0) 1622-723300  
Fax: +44 (0) 1622-728703

75922  
©Parker Hannifin Corporation 1997, 2002  
Printed in U.S.A.

## Maintenance

### Final Filter Maintenance

The final membrane filter should also be replaced once a year under normal operating conditions. The Balston Grade 95 final filter is located inside the 75-83 and is easily replaced by first removing the 2 front panel screws. Then, remove the compression fittings using a 1/2" and a 7/16" open end wrench. Slide the 1/2" nut and plastic ferrule off both ends of the disposable filter. Discard the plastic ferrules and worn DFU. The 1/2" compression nuts are reusable; do not discard. The replacement final filter kit (P/N 75922), which is shipped with 1/4" plastic ferrules, can now be installed. Install the DFU with the flow arrow pointing to the outlet. Tighten the compression fittings one turn after finger tight. Do not use metallic ferrules with the disposable filter unit, as these will damage the plastic connections. Leak test the 75-83 after installing the GS Grade 95 final filter.



Parker Hannifin Corporation  
Filtration and Separation Division  
100 Ames Pond Drive, P.O. Box 1262  
Tewksbury, MA 01876-0962  
Tel: 978-858-0505 Fax: 978-858-0625

Parker Hannifin plc  
Hermitage Court, Hermitage Lane  
Maidstone, Kent ME16 9NT, England  
Tel: +44 (0) 1622-723300  
Fax: +44 (0) 1622-728703

75922  
©Parker Hannifin Corporation 1997, 2002  
Printed in U.S.A.

## Maintenance

### Final Filter Maintenance

The final membrane filter should also be replaced once a year under normal operating conditions. The Balston Grade 95 final filter is located inside the 75-83 and is easily replaced by first removing the 2 front panel screws. Then, remove the compression fittings using a 1/2" and a 7/16" open end wrench. Slide the 1/2" nut and plastic ferrule off both ends of the disposable filter. Discard the plastic ferrules and worn DFU. The 1/2" compression nuts are reusable; do not discard. The replacement final filter kit (P/N 75922), which is shipped with 1/4" plastic ferrules, can now be installed. Install the DFU with the flow arrow pointing to the outlet. Tighten the compression fittings one turn after finger tight. Do not use metallic ferrules with the disposable filter unit, as these will damage the plastic connections. Leak test the 75-83 after installing the GS Grade 95 final filter.



Parker Hannifin Corporation  
Filtration and Separation Division  
100 Ames Pond Drive, P.O. Box 1262  
Tewksbury, MA 01876-0962  
Tel: 978-858-0505 Fax: 978-858-0625

Parker Hannifin plc  
Hermitage Court, Hermitage Lane  
Maidstone, Kent ME16 9NT, England  
Tel: +44 (0) 1622-723300  
Fax: +44 (0) 1622-728703

75922  
©Parker Hannifin Corporation 1997, 2002  
Printed in U.S.A.